



RF-W202DDB

| | | |
|------------------|--------------------------|--|
| Product | Model | RF-W202DDB |
| | Type | Binocular gun ball linkage module |
| System | Main processor | T23 |
| | Operating system | Embedded LINUX operating system |
| Video | Imaging device | 1/3.2 CMOS Sensor |
| | Video coding standard | H.264 |
| | System standard | PAL 50HZ/NTSC 60HZ |
| | Effective resolution | 1920*1080P |
| | Video frame rate | self-adaptation |
| | Video stream | 135kbps-2048kbps |
| | Minimum illumination | Daytime mode 1Lux, night vision mode 0.01Lux |
| | Day-night mode | Auto |
| | Capture function | support |
| Audio | Coding standard | G.711U |
| | Audio input | External microphone MIC, analog MIC with signal to noise ratio of 42DB |
| | Audio output | External 8Ω/MAX2W speaker |
| | Voice call | Supports full-duplex voice calls |
| Video management | Video recording mode | Alarm video, timing video |
| | Video preservation | TFCard/PC /NVR |
| | Cloud storage | support |
| Alarm | Alarm detection | Mobile, humanoid, cry detection |
| | Audible and visual alarm | Supported, with dual light board, support sound and light alarm |
| | Alarm voice | Supports text-to-speech and custom speech functions |
| | Alarm linkage | Linkage video, capture picture |
| PTZ | Preset bit | Supports six preset bits |
| | Tracking function | Support humanoid tracking |

| | | |
|---------|---------------------|--|
| Network | RJ45 | HTTP,TCP/IP,IPV4,UPNP,RTSP, UDP, SMTP, NTP, DHCP, DNS, IPFilter,IPSearch(Support P6S IP camera, DVR, NVS and etc.) |
| | Wifi | 2.4G antenna support, 802.11b/g/n |
| | BLE | Supports Bluetooth network distribution function |
| | Protocol | P6S |
| Sleep | Sleep function | Supports timing sleep and instant sleep functions to maintain user privacy |
| APP | APP | P6SLite |
| Other | TFcard capacity | Up to 128GB(universal FAT32 format) |
| | Operating voltage | DC5V |
| | Working current | 530mA ±10mA |
| | Working environment | -20°C--- 55°C |
| Size | Main board | 52mm*38mm |
| | Sub board | 38*38mm(suitable for gun ball products)/28*28mm (suitable for binocular shaking machine products) |
| | ICR/LENS pit ch-row | 20mm |