



RF-W503DD

Product	Model	RF-W503DD
	Type	Binocular gun ball linkage module
System	Main processor	T23
	Operating system	Embedded LINUX operating system
Video	Imaging device	1/3.2 CMOS Sensor
	Video coding standard	H.264
	System standard	PAL 50HZ/NTSC 60HZ
	Effective resolution	1920*1080P
	Video frame rate	self-adaptation
	Video stream	135kbps-2048kbps
	Minimum illumination	Daytime mode 1Lux, night vision mode 0.01Lux
	Day-night mode	Auto
	Capture function	support
Audio	Coding standard	G.711U
	Audio input	External microphone MIC, analog MIC with signal to noise ratio of 42DB
	Audio output	External 8Ω/MAX2W speaker
	Voice call	Supports full-duplex voice calls
Video management	Video recording mode	Alarm video, timing video
	Video preservation	TFCard/PC /NVR
	Cloud storage	support
Alarm	Alarm detection	Mobile, humanoid, cry detection
	Audible and visual alarm	Supported, with dual light board, support sound and light alarm
	Alarm voice	Supports text-to-speech and custom speech functions
	Alarm linkage	Linkage video, capture picture
PTZ	Preset bit	Supports six preset bits
	Tracking function	Support humanoid tracking
Network	RJ45	HTTP,TCP/IP,IPV4,UPNP,RTSP, UDP, SMTP, NTP, DHCP, DNS, IPFilter,IPSearch(Support P6S IP camera, DVR, NVS and etc.)
	Wifi	2.4G antenna support, 802.11b/g/n
	BLE	Supports Bluetooth network distribution function
	Protocol	P6S
Sleep	Sleep function	Supports timing sleep and instant sleep functions to maintain user privacy
APP	APP	P6SLite
Other	TFCard capacity	Up to 128GB(universal FAT32 format)

	Operating voltage	DC5V
	Working current	530mA ±10mA
	Working environment	-20°C--- 55°C
Size	Main board	52mm*38mm
	Sub board	38*38mm(suitable for gun ball products)/28*28mm (suitable for binocular shaking machine products)
	ICR/LENS pit ch-row	20mm

REFACO